



DEPARTMENT OF PERMITTING, ENVIRONMENT, AND REGULATORY
AFFAIRS (PERA)
BOARD AND CODE ADMINISTRATION DIVISION
NOTICE OF ACCEPTANCE (NOA)

MIAMI-DADE COUNTY
PRODUCT CONTROL SECTION
11805 SW 26 Street, Room 208
Miami, Florida 33175-2474
T (786) 315-2590 F (786) 315-2599
www.miamidade.gov/pera/

Black Mountain Door, LLC
310 Flint Drive,
MT. Sterling, KY. 40353

SCOPE:

This NOA is being issued under the applicable rules and regulations governing the use of construction materials. The documentation submitted has been reviewed and accepted by Miami-Dade County PERA -Product Control Section to be used in Miami Dade County and other areas where allowed by the Authority Having Jurisdiction (AHJ).

This NOA shall not be valid after the expiration date stated below. The Miami-Dade County Product Control Section (In Miami Dade County) and/or the AHJ (in areas other than Miami Dade County) reserve the right to have this product or material tested for quality assurance purposes. If this product or material fails to perform in the accepted manner, the manufacturer will incur the expense of such testing and the AHJ may immediately revoke, modify, or suspend the use of such product or material within their jurisdiction. PERA reserves the right to revoke this acceptance, if it is determined by Miami-Dade County Product Control Section that this product or material fails to meet the requirements of the applicable building code.

This product is approved as described herein, and has been designed to comply with the Florida Building Code, including the High Velocity Hurricane Zone.

DESCRIPTION: Firedoor Series "S-8080-HMD" Outswing Commercial Steel Door

APPROVAL DOCUMENT: Drawing No. **W06-31 Rev E**, titled "Firedoor series S-8080-HMD-F" Out-Swing Commercial STL. DR.", sheet 1 through 7 of 7, dated 04-15-06 and last revised on MAR 22, 2012, prepared by Al-Farooq Corporation, signed and sealed by Javad Ahmad, P. E., bearing the Miami-Dade County Product Control Revision stamp with the Notice of Acceptance number and expiration date by the Miami-Dade County Product Control Section.

MISSILE IMPACT RATING: Large and Small Missile Impact Resistant

Limitation:

1. Frame Jambs and Header are to be grout filled.
2. The 3/8" Hilti Sleeve anchors into grouted masonry is applicable to side Jambs only.

LABELING: Each unit shall bear a permanent label with the manufacturer's name or logo, city, state and series and following statement: "Miami-Dade County Product Control Approved", noted herein.

RENEWAL of this NOA shall be considered after a renewal application has been filed and there has been no change in the applicable building code negatively affecting the performance of this product.

TERMINATION of this NOA will occur after the expiration date or if there has been a revision or change in the materials, use, and/or manufacture of the product or process. Misuse of this NOA as an endorsement of any product, for sales, advertising or any other purposes shall automatically terminate this NOA. Failure to comply with any section of this NOA shall be cause for termination and removal of NOA.

ADVERTISEMENT: The NOA number preceded by the words Miami-Dade County, Florida, and followed by the expiration date may be displayed in advertising literature. If any portion of the NOA is displayed, then it shall be done in its entirety.

INSPECTION: A copy of this entire NOA shall be provided to the user by the manufacturer or its distributors and shall be available for inspection at the job site at the request of the Building Official.

This NOA **revises & renews** NOA # **09-0923.12** (Former **FireDoor by Amweld International, LLC**) and consists of this page 1 and evidence pages E-1 & E-2, as well as approval document mentioned above.

The submitted documentation was reviewed by **Ishaq I. Chanda, P.E.**



NOA No 12-0323.07
Expiration Date: September 21, 2014
Approval Date: July 19, 2012
Page 1

7/12/12

NOTICE OF ACCEPTANCE: EVIDENCE SUBMITTED

A. DRAWINGS

1. Manufacturer's die drawings and sections (transferred from file # **09-0923.12**)
2. Drawing No. **W06-31 Rev E**, titled "Firedoor series S-8080-HMD-F" Out-Swing Commercial STL. DR.", sheet 1 through 7 of 7, dated 04-15-06 and last revised on MAR 22, 2012, prepared by Al-Farooq Corporation, signed and sealed by Javad Ahmad, P.E.

Note: This revision consists of FBC 2010 notes & company name change only.

B. TESTS (transferred from file # **09-0923.12/ # **06-0512.04**)**

1. Test reports on
 - 1) Air Infiltration Test, per FBC TAS 202-94
 - 2) Uniform Static Air Pressure Test Loading per FBCTAS 202-94
 - 3) Water Resistance Test, per FBC TAS 202-94
 - 4) Forced Entry Resistance Test, per FBC TAS 202-94
 - 5) Large Missile Impact Test, FBC TAS 201-94
 - 6) Cyclic Loading Test, per FBC TAS 203-94

Along with marked-up drawings and installation diagram of outswing steel door, prepared by Fenestration Testing Laboratory, Inc., Test Report No. FTL **4844**, dated 03/27/06, signed and sealed by Edmundo Largaespada, P.E.

Note: The above test report has been revised with addendum letters dated June 23, 2006 and a by Fenestration Testing Laboratory, Inc., Test Report FTL 4844, signed and sealed by Edmundo Largaespada, P.E.

2. Additional referenced test report # FTL 1865 dated Nov. 25, 1997, issued by Fenestration testing Lab per SFBC PA 201, 202 and 203-94, signed and sealed by late Gilbert Diamond, P.E.

C. CALCULATIONS

1. Anchor verification dated June 24, 2009 and last revised on Apr 06, 2010, prepared by Al-Farooq Corporation, complying w/ FBC 2007, signed and sealed by Javad Ahmad, P.E. (submitted under file # **09-0923.12**).

D. QUALITY ASSURANCE

1. Miami Dade Department of Permitting, Environment, and Regulatory Affairs (PERA).

E. MATERIAL CERTIFICATIONS

1. Tensile Test report No. FTL 4932, dated April 27, 2006, issued by Fenestration Testing Laboratory, Inc., as per ASTM E-8, signed & sealed by Edmundo Largaespada, P.E.
2. Notice of Acceptance No. **11-0926.07** issued to Dyplast Product, LLC (Former Apache Products Company) for "EPS-Expanded Polystyrene Insulation", expiring on 01/11/17



Ishaq I. Chanda, P.E.
Product Control Examiner
NOA No 12-0323.07

Expiration Date: September 21, 2014
Approval Date: July 19, 2012


NOTICE OF ACCEPTANCE: EVIDENCE SUBMITTED

F. STATEMENTS

1. Statement letter of conformance to FBC 2010 and letter of no financial interest, prepared by Al Farooq Corporation, dated 03/14/12, signed and sealed by Javad Ahmad, P.E.
2. Statement letter of compliance, as part of above referenced test report, issued by Fenestration testing lab.
3. Official "Black Mountain Door" press release dated June 21, 2012 stating acquiring the assests, technology, "Firedoor"™ "brand and intellectual properties of Amweld International.
4. Statement letter dated May 08, 2012 stating acquiring all the assets of Amweld international, issued by Black Mountain door, signed by Jason W. Lisewski, V.P. Black Mountain Door.
5. Statement letter dated January 26, 2012 issued by Amweld International, LLC of notification of the assets of Amweld International was purchased by American Doors, LLC DBA Black Mountain Door, Mt. Sterling, KY, signed by David Earnshaw, trustee for Amweld International.
6. Copy of certificate of formation of "American Doors, LLC" issued by State of Delaware dated 10-11-11, signed by Jeffery W. Bullock, Secretary of State.
7. Copy of certificate of Amendment of "American Doors, LLC" changing name to "Black Mountain Door, LLC", issued by State of Delaware dated 06-20-12, signed by Jeffery W. Bullock, Secretary of State.




G. OTHER

1. This NOA revises NOA # 09-0923.12(Former FireDoor by Amweld International, LLC), expired on September 21, 2011.
2. E-mail response dated July 10 & 11, 2012 & documents from Mr. J. Lisewski, V.P. Black Mountain Door.



Ishaq I. Chanda, P.E.
Product Control Examiner
NOA No 12-0323.07

Expiration Date: September 21, 2014
Approval Date: July 19, 2012



TYPICAL ANCHORS: SEE ELEV. FOR SPACING

3/8" DIA. CARBON STEEL SLEEVE ANCHOR HILT
 DIRECTLY INTO CONC. OR MASONRY
 1-5/8" MIN. EMBED INTO CONCRETE
 1-5/8" MIN. EMBED INTO MASONRY (@ JAMBS ONLY)
 3-3/4" MIN. EDGE DISTANCE

3/8" DIA. SMS OR MACHINE BOLTS (GRADE 2 CRS)
 INTO METAL STRUCTURES (STEEL OR ALUMINUM 1/8" MIN. THICK.)
 STEEL : $F_y = 36$ KSI MIN.
 ALUMINUM : 6063-T5 MIN.
 (STEEL IN CONTACT WITH ALUMINUM TO BE PLATED OR PAINTED)

'T' ANCHORS
 7-7/8" MIN. EMBEDDED BETWEEN BLOCKS (@ JAMBS ONLY)
 SEE SHEET 5 FOR DETAIL

TYPICAL ANCHORS @ THRESHOLD:

1/4" DIA. ULTRACON BY 'ELCO' ($F_u = 177$ KSI, $F_y = 155$ KSI)
 DIRECTLY INTO CONCRETE
 WITH 1-1/4" MIN. EMBED INTO CONC.
 2-1/2" MIN. EDGE DISTANCE

CONCRETE $f'_c = 3000$ PSI MIN.
 C-90 FILLED MASONRY BLOCK $f'_m = 2000$ PSI MIN.

PRODUCT REVISED
 to comply with the Florida
 Building Code
 Amendment No. 12-0323-07
 Expiration Date 9/21/14
 J. Shag (Signature)
 J. Shag (Signature)

METAL STRUCTURES NOT BY BLACK MOUNTAIN DOOR
 MUST SUPPORT LOADS IMPOSED BY DOOR SYSTEM AND
 TRANSFER THEM TO THE BUILDING STRUCTURE.

SEALANT:
 ALL JOINTS AND CORNERS SEALED WITH SILICONE.

Engr: JAVAD AHMAD
 CIVIL
 FLA. PE # 70592
 C.A.N. 3538
 MAR 22 2012

AL-FAROOQ CORPORATION
 ENGINEERS & PRODUCT DEVELOPMENT
 1235 S.W. 87 AVE
 MIAMI, FLORIDA 33174
 TEL. (305) 264-8100 FAX. (305) 262-6978
 COMP-ANL W06-31FDC





FIREDOOR S-8080F-HMD-F OUT-SWING COMMERCIAL ST. DR.
BLACK MOUNTAIN DOOR, LLC.
 310 FLINT DRIVE
 MT. STERLING, KY 40353
 TEL. (855) 370-4580 FAX. (859) 762-0852

revisions:	no	date	by	description
	A	07.13.06	REV. PER BCCO COMMENTS	
	B	06.16.09	UPDATED FOR 2007 FBC	
	C	10.20.09	NO CHANGE THIS SHEET	
	D	03.23.10	REV. PER BCCO COMMENTS	
	E	03.15.12	UPDATED TO 2010 FBC	

date: 04-15-06	scale: 3/8" = 1"	dr. by: HAMID	chk. by:
----------------	------------------	---------------	----------

drawing no.	W06-31
-------------	--------

sheet 2 of 7



GROUT REQD. AT HEAD/JAMBS WITH HAT ANCHOR SPACER
GROUT NOT REQD. AT JAMBS WITH PIPE ANCHORS
SEE DETAILS ON SHEET 4.

PRODUCT REVISION
to comply with the Florida
Building Code
Assignment No. 12-0323-07
Revision Date 9/21/14
By: [Signature]
Checked By: [Signature]

Engr: JAVAD AHMAD
CIVIL
FLA. PE # 70592
C.A.N. 3538

MAR 22 2012

AL-FAROOQ CORPORATION
ENGINEERS & PRODUCT DEVELOPMENT
1235 S.W. 87 AVE
MIAMI, FLORIDA 33174
TEL. (305) 264-8100 FAX. (305) 262-6978
COMP-ANL\W06-31FDC



FIREDOOR S-8080F-HMD-F OUT-SWING COMMERCIAL ST. DR.

BLACK MOUNTAIN DOOR, LLC.
310 FLINT DRIVE
MT. STERLING, KY 40353
TEL. (855) 370-4580 FAX. (859) 762-0852

revisions:	
no	date
A	07.13.06
B	06.16.09
C	10.20.09
D	03.23.10
E	03.15.12


date:	04-15-06
scale:	3/8" = 1"
dr. by:	HAMID
chk. by:	

drawing no.	W06-31
sheet	3 of 7




BOTTOM CORNER ANCHORS DETAIL

PRODUCT REVISED
 in compliance with the Florida
 Building Code
 Acceptance No. 12-0323-07
 Expiration Date 9/2014
 By Shahid Chaudhry
 Moham Data Product Control




FRAME WITH GROUT OPTION


FRAME WITHOUT GROUT OPTION



MASONRY 'T' ANCHOR OPTION
 SEE ELEV. FOR SPACING



Engr: JAVAD AHMAD
 CIVIL
 FLA. PE # 70592
 C.A.N. 3538
 MAR 22 2012



AL-FAROOQ CORPORATION
 ENGINEERS & PRODUCT DEVELOPMENT
 1235 S.W. 87 AVE
 MIAMI, FLORIDA 33174
 TEL. (305) 264-8100 FAX. (305) 262-6978
 COMP-ANL W06-31FDC


FIREDOOR S-8080F-HMD-F OUT-SWING COMMERCIAL ST. DR.

BLACK MOUNTAIN DOOR, LLC.
 310 FLINT DRIVE
 MT. STERLING, KY 40353
 TEL. (855) 370-4580 FAX. (859) 762-0852

revisions:		no.	date	by	description
A	07.13.06	REV. PER BCCO COMMENTS			
B	06.16.09	UPDATED FOR 2007 FBC			
C	10.20.09	NO CHANGE THIS SHEET			
D	03.23.10	REV. PER BCCO COMMENTS			
E	03.15.12	UPDATED TO 2010 FBC			

date:	04-15-06
scale:	3/8" = 1"
dr. by:	HAMID
chk. by:	

drawing no. **W06-31**
 sheet 4 of 7



LOCK OPTION #5

PRODUCT REVISION
in compliance with the Florida
Building Code
Acceptance No. 12-0323-07
Expiration Date 9/21/14
By: *[Signature]*
Miami Date Product Control

Engr: JAVAD AHMAD
CIVIL
FLA. PE # 70592
C.A.N. 3538

MAR 22 2012

afc

AL-FAROOQ CORPORATION
ENGINEERS & PRODUCT DEVELOPMENT
1235 S.W. 87 AVE
MIAMI, FLORIDA 33174
TEL (305) 264-8100 FAX (305) 262-6978
COMP-ANL\W06-31FDC

FREEDOR S-8080F-HMD-F OUT-SWING COMMERCIAL ST. DR.
BLACK MOUNTAIN DOOR, LLC.
310 FLINT DRIVE
MT. STERLING, KY 40353
TEL. (855) 370-4580 FAX. (859) 762-0852

revisions:	no	date	by	description
	A	07.13.06		REV. PER BCCO COMMENTS
	B	06.16.09		UPDATED FOR 2007 FBC
	C	10.20.09		NO CHANGE THIS SHEET
	D	03.23.10		REV. PER BCCO COMMENTS
	E	03.15.12		UPDATED TO 2010 FBC

date: 04-15-06
scale: 3/8" = 1"
dr. by: HAMID
chk. by:

drawing no.
W06-31

sheet 5 of 7

LOCK OPTIONS:

ACTIVE LEAF:

OPTION #1:

'SCHLAGE' AL OR 'SCHLAGE' D SERIES SURFACE MOUNT ST/ST CYLINDRICAL LOCK KEY OPERATE ON EXTERIOR & THUMB TURN ON INTERIOR AT 38" TO 40-3/8" FROM BOTTOM.

4-7/8" LONG ST. STEEL STRIKE PLATE AT 38" TO 40-3/8" FROM BOTTOM

'SCHLAGE' B SERIES SURFACE MOUNT DEAD BOLT LOCK, KEY OPERATE ON EXTERIOR & THUMB TURN ON INTERIOR, AT 48" FROM BOTTOM.

2-3/4" LONG ST. STEEL STRIKE PLATE AT 48" FROM BOTTOM

OPTION #2:

'YALE' 5300LN OR 'YALE' 5400 LN SERIES SURFACE MOUNT ST/ST CYLINDRICAL LOCK KEY OPERATE ON EXTERIOR & THUMB TURN ON INTERIOR AT 38" TO 40-3/8" FROM BOTTOM.

4-7/8" LONG ST. STEEL STRIKE PLATE AT 38" TO 40-3/8" FROM BOTTOM

'YALE' 3600 SURFACE MOUNT DEAD BOLT LOCK, KEY OPERATE ON EXTERIOR & THUMB TURN ON INTERIOR, AT 48" FROM BOTTOM.

2-3/4" LONG ST. STEEL STRIKE PLATE AT 48" FROM BOTTOM

OPTION #3:

'PARKER' SL7160 SERIES SURFACE MOUNT ST/ST CYLINDRICAL LOCK KEY OPERATE ON EXTERIOR & THUMB TURN ON INTERIOR AT 38" TO 40-3/8" FROM BOTTOM.

4-7/8" LONG ST. STEEL STRIKE PLATE AT 38" TO 40-3/8" FROM BOTTOM

'SCHLAGE' B SERIES SURFACE MOUNT DEAD BOLT LOCK, KEY OPERATE ON EXTERIOR & THUMB TURN ON INTERIOR, AT 48" FROM BOTTOM.

2-3/4" LONG ST. STEEL STRIKE PLATE AT 48" FROM BOTTOM

OPTION #4:

'SCHLAGE' L OR 'YALE' 8700 SERIES SURFACE MOUNT ST/ST MORTISE LOCK WITH A DEAD BOLT, KEY OPERATE ON EXTERIOR & THUMB TURN ON INTERIOR AT 38" TO 40-3/8" FROM BOTTOM.

4-7/8" LONG ST. STEEL STRIKE PLATE AT 38" TO 40-3/8" FROM BOTTOM

INACTIVE LEAF (FOR OPTION #1, 2, 3 AND 4)

ROCKWOOD 555 FLUSHBOLTS MOUNTED 12" FROM EACH END OF DOOR TO CENTERLINE


4-7/8" X 1-1/4" X 1/16" ASA STRIKE

NOTE: TOP AND BOTTOM FLUSH BOLTS MUST BE ENGAGED DURING PERIODS OF HURRICANE WARNING.


ACTIVE/INACTIVE LEAF:

OPTION #5:


'VON DUPRIN' 9927 OR 'YALE' 7110 SURFACE VERTICAL ROD ST/ST PANIC DEVICE ON INTERIOR ST. STEEL LEVER TYPE HANDLE WITH KEY OPERATED ON EXTERIOR AT 38" TO 40-3/8" FROM BOTTOM.



OPTION #1, 2, 3
CYLINDRICAL LOCK
+ DEAD BOLT



OPTION #4
MORTISE LOCK
+ DEAD BOLT



OPTION #5

ITEM NO.	PART NO.	QUANTITY	DESCRIPTION	MATERIAL	MANF./SUPPLIER/REMARKS
1	-	AS REQD.	FRAME HEAD (5-3/4" X 2")	STEEL	16 GA. (.053") MIN. Fy = 43.0 KSI
1A	-	AS REQD.	FRAME HEAD (5-3/4" X 4")	STEEL	16 GA. (.053") MIN. Fy = 43.0 KSI
1B	-	AS REQD.	FRAME HEAD (8-3/4" X 4")	STEEL	16 GA. (.053") MIN. Fy = 43.0 KSI
1C	-	AS REQD.	FRAME HEAD (5-3/4" X 1-1/4")	STEEL	16 GA. (.053") MIN. Fy = 43.0 KSI
2	-	AS REQD.	FRAME JAMB (5-3/4" X 2")	STEEL	16 GA. (.053") MIN. Fy = 43.0 KSI
2A	-	AS REQD.	FRAME JAMB (8-3/4" X 2")	STEEL	16 GA. (.053") MIN. Fy = 43.0 KSI
2B	-	AS REQD.	FRAME JAMB (5-3/4" X 1-1/4")	STEEL	16 GA. (.053") MIN. Fy = 43.0 KSI
3	2005	1	THRESHOLD	ALUMINUM	PEMKO
4	-	AS REQD.	BOLT SPACER (2" FRAME)	STEEL	2" X 2-5/8" X 18 GA.
4A	-	AS REQD.	BOLT SPACER (1-1/4" FRAME)	STEEL	2" X 1-7/8" X 18 GA.
5	-	-	ASTRAGAL	-	1-1/4" X 12 GA.
5A	305	-	SPLIT ASTRAGAL	-	PEMKO
6	-	-	DOOR	STEEL	18 GA.(.045") OR 16 GA.(.053") MIN. Fy = 43.0 KSI
7	-	2/ INACTIVE LEAF	SERIES 555 FLUSH BOLTS (OPTIONS 1, 2, 3 & 4)	STEEL	ROCKWOOD
8	-	OPTIONAL	FRAME GROUT	CONC.	3000 PSI MIN.
9	-	8/ LEAF	HAT STIFFENER IN PAIRS (4 ROWS VERTICAL)	STEEL	22 GA.
10	-	1	POLYSTYRENE CORE	-	'DYPLAST PRODUCTS LLC' W/ CURRENT NOA
10A	-	1	THERMAL INSULATION	-	OWENS CORNING RA-24 BATT
11	-	1/ RAIL	TOP AND BOTTOM RAIL CHANNEL (FULL LENGTH)	STEEL	13/16 X 1-21/32 X 13/16 X 16 GA.
12	-	1/ RAIL	TOP RAIL CHANNEL (FULL LENGTH)	STEEL	11/16 X 1-1/2 X 11/16 X 18 GA.
13	-	2/ HINGE	HINGE REINFORCEMENT (FRAME/DOOR)	STEEL	1-1/4" X 10" X 3/16"
14	S88	1	HEAD/JAMB WEATHERSTRIP	VINYL	PEMKO
16	1279	3/ LEAF	MORTISE HINGES	STEEL	HAGER
17	-	2/ LOCK	LOCK REINFORCEMENT PLATE	-	1-1/4" W X 2-3/4" HIGH X 12 GA.
18	-	1/ STRIKE	STRIKE REINFORCEMENT	-	1-3/8" X 6-1/2" X 16 GA.


HINGES:

STEEL MORTISE HINGE 1279
AT 7-1/4" TO 9-3/4" FROM TOP TO CL OF HINGE
AT 7-1/4" TO 12-5/8" FROM BOTTOM TO CL OF HINGE
(1) CENTER HINGE EQUALLY SPACED FROM TOP & BOTTOM HINGE

DOOR EDGE CONSTRUCTION OPTIONS:


OPTION #1:

LOCK SEAM EDGE CONSTRUCTION



OPTION #1:

BUTT SEAM EDGE CONSTRUCTION



PRODUCT REVISED
as complying with the Florida
Building Code
Acceptance No. 12-0323.07
Expiration Date 9/2/14
By: [Signature]
Manual Date: Product Control

Engr: JAVAD AHMAD
CIVIL
FLA. PE # 70592
C.A.N. 3538
MAR 2 2012

af c
AL-FAROOQ CORPORATION
ENGINEERS & PRODUCT DEVELOPMENT
1235 S.W. 87 AVE
MIAMI, FLORIDA 33174
TEL. (305) 264-8100 FAX. (305) 262-6978
COMP-ANL\W06-31FDC


FREDOOR S-8080F-HMD-F OUT-SWING COMMERCIAL ST. DR.
BLACK MOUNTAIN DOOR, LLC.
310 FLINT DRIVE
MT. STERLING, KY 40353
TEL. (855) 370-4580 FAX. (859) 762-0852

no	date	by	description
A	07.13.06	REV. PER BCCO COMMENTS	
B	06.16.09	UPDATED FOR 2007 FBC	
C	10.20.09	LOCK & HINGE LOCATIONS REV.	
D	03.23.10	REV. PER BCCO COMMENTS	
E	03.15.12	UPDATED TO 2010 FBC	


date: 04-15-06
scale: 3/8" = 1"
dr. by: HAMID
chk. by:

drawing no.
W06-31


sheet 6 of 7




(2A) FRAME JAMB




(1) (2) FRAME HEAD/JAMB




(1C) (2B) FRAME HEAD/JAMB




(1B) FRAME HEAD




(1A) FRAME HEAD




(9) HAT CHANNEL REINFORCING



(16) .134" THICK STEEL HINGE




(4A)




(4)


HAT ANCHOR SPACER



(3) BUMPER THRESHOLD




FRAME CORNERS



INTERLOCKED TABS

PRODUCT REVIEWED
as complying with the Florida
Building Code
Acceptance No. 12-0323.07
Expiration Date SEP 21, 2014
By: [Signature]
Manual Date Product Control

Engr: JAVAD AHMAD
CIVIL
FLA. PE # 70592
C.A.N. 3538
MAR 22 2012



AL-FAROOQ CORPORATION
ENGINEERS & PRODUCT DEVELOPMENT
1235 S.W. 87 AVE
MIAMI, FLORIDA 33174
TEL (305) 264-8100 FAX (305) 262-6978
COMP-ANL\W06-31FDC

FREEDOR S-8080F-HMD-F OUT-SWING COMMERCIAL ST. DR.

BLACK MOUNTAIN DOOR, LLC.
310 FLINT DRIVE
MT. STERLING, KY 40353
TEL (855) 370-4580 FAX (859) 762-0852

no.	date	by	description
A	07.13.06	REV. PER BCCO COMMENTS	REV. PER BCCO COMMENTS
B	06.16.09	UPDATED FOR 2007 FBC	NO CHANGE THIS SHEET
C	10.20.09	NO CHANGE THIS SHEET	REV. PER BCCO COMMENTS
D	03.23.10	REV. PER BCCO COMMENTS	UPDATED TO 2010 FBC
E	03.15.12	REV. PER BCCO COMMENTS	UPDATED TO 2010 FBC

date: 04-15-06

scale: 3/8" = 1"

dr. by: HAMID

chk. by:

drawing no.
W06-31

sheet 7 of 7